

LORO-X COMPOSITE DOUBLE SOCKET DN 100

LORO-Composite Pipe Double Socket DN 100

Descrizione

LORO-X compound pipe double socket (projecting), consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN100




Dati articolo

Codice EAN	4038088025383
Classe ETIM	EC003024
Diametro nominale	DN 100
Misure esterne (AxLxP)	133 x 133 x 180 mm
Peso	2,00 Kg (STK)
Gruppo prodotti	3
Numero tariffa doganale	73089098
Materiale / Colore	Stahl feuerverzinkt, Silber

Note d'uso

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Download



Alles online

[Istruzioni di installazione \(PDF\)](#)

CAD 2D (DXF)

[Disegno dimensionale \(PDF\)](#)

CAD (DWG)

[Brochure \(PDF\)](#)