


LORO-X COMPOSITE DOUBLE SOCKET DN 125

LORO-Composite Pipe Double Socket DN 125

Beschrijving

LORO-X compound pipe double socket (projecting), consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN125



Artikelgegevens

EAN-code	4038088044575
ETIM Klasse	EC003024
Nominale diameter	DN 125
Buitenafmetingen (HxBxL)	168 x 168 x 190 mm
Gewicht	4,30 Kg (STK)
Productgroep	3
Douanetariefnumme r	73089098
Materiaal / Kleur	Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Maattekening \(PDF\)](#)
[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)