

LORO-VERBUNDROHR M.R.-ÖFFN.VERS.500 MM,

LORO-Composite Pipe with cleaning opening 500 mm DN 70

Descripción

LORO-X compound pipe with clean-out opening (recessed), consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 500 mm, DN70



Datos del artículo

Código EAN 4038088025406

Clase ETIM EC010323

Diámetro nominal DN 70

Longitud/grado nominal 500

Medidas exteriores (AxAxL) 102 x 102 x 555 mm

Peso 5,00 Kg (STK)


Grupo de productos 3

Número de arancel aduanero 73063012

Material / Color Stahl feuerverzinkt, Silber

Nota de uso

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Dibujo dimensional \(PDF\)](#)

[CAD \(DWG\)](#)

[Folleto \(PDF\)](#)