

LORO-X COMPOSITE TRANSITION PIPE CONCENTR DN 50/100

LORO-Composite transition pipe

Beskrivningstext

LORO-X compound pipe transition pipe (concentric reducer) consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN50/100




Artikeldata

EAN-kod	4038088042717
ETIM-klass	EC003024
Nominell diameter	DN 50, DN 100
Yttermått (HxBxL)	133 x 133 x 198 mm
Vikt	1,80 Kg (STK)
Produktgrupp	3
Tullnummer	73089098
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)

CAD 2D (DXF)

[Måttitning \(PDF\)](#)

CAD (DWG)

[Broschyr \(PDF\)](#)