

LORO-X COMPOSITE TRANSITION PIPE CONCENTR DN 100/125

LORO-Composite transition pipe DN 100/125

Popis

LORO-X compound pipe transition pipe (concentric reducer) consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN100/125




Údaje o artiklu

EAN kód	4038088025512
ETIM třída	EC003024
Jmenovitý průměr	DN 100, DN 125
Vnější rozměry (VxŠxD)	168 x 168 x 230 mm
Hmotnost	3,70 Kg (STK)
Skupina produktů	3
Celní sazebník	73089098
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Ke stažení



Alles online

[Návod k instalaci \(PDF\)](#)

CAD 2D (DXF)

[Výkres rozměrů \(PDF\)](#)

CAD (DWG)

[Prospekt \(PDF\)](#)