

LORO-X COMPOSITE TRANSITION PIPE CONCENTR DN 125/150

LORO-Composite transition pipe DN 125/150

Description

LORO-X compound pipe transition pipe (concentric reducer) consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN125/150




Données de l'article

Code EAN	4038088025529
Classe ETIM	EC003024
Diamètre nominal	DN 125, DN 150
Dimensions extérieures (HxLxP)	219 x 219 x 225 mm
Poids	5,10 Kg (STK)
Groupe de produits	3
Numéro tarifaire douanier	73089098
Matériau / Couleur	Stahl feuerverzinkt, Silber

Note d'utilisation

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Téléchargements



Alles online

[Notice d'installation \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Dessin dimensionnel \(PDF\)](#)
[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)