


LORO-X COMPOSITE TRANSITION PIPE CONCENTR DN 150/200

LORO-Composite transition pipe

Текст за тръжна документация

LORO-X compound pipe transition pipe (concentric reducer) consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN150/200



Данни за артикула

ЕАН код	4038088038215
ЕТИМ клас	EC003024
Номинален диаметър	DN 150, DN 200
Външни размери (ВxШxД)	273 x 273 x 315 mm
Тегло	8,20 Kg (STK)
Продуктова група	3
Митнически тарифен номер	73089098
Материал / Цвят	Stahl feuerverzinkt, Silber

Забележка за употреба

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr

Изтегляния



Alles online

[Инструкция за монтаж \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[CAD чертеж \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Брошура \(PDF\)](#)

[BIM 3D \(STEP\)](#)