

## LORO-X COMPOSITE TRANSITION PIPE CONCENTR DN 80/100

### LORO-Composite transition pipe DN 80/100

#### Description

LORO-X compound pipe transition pipe (concentric reducer) consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN 80/100




#### Article information

|                              |                             |
|------------------------------|-----------------------------|
| EAN Code                     | 4038088049600               |
| ETIM Class                   | EC003024                    |
| Nominal diameter             | DN 80, DN 100               |
| Outside measurements (HxWxL) | 133 x 133 x 200 mm          |
| Weight                       | 2,00 Kg (STK)               |
| Product group                | 3                           |
| Customs tariff number        | 73089098                    |
| Material / Color             | Stahl feuerverzinkt, Silber |

#### Usage note

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



#### Downloads



Alles online

[Installation \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[CAD drawing \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)