

LORO-X COMPOSITE TRANSITION PIPE CONCENTR DN 80/100

LORO-Composite transition pipe DN 80/100

Kuvaus

LORO-X compound pipe transition pipe (concentric reducer) consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN 80/100




Tuotetiedot

EAN-koodi	4038088049600
ETIM-luokka	EC003024
Nimellishalkaisija	DN 80, DN 100
Ulkomitat (KxLxS)	133 x 133 x 200 mm
Paino	2,00 Kg (STK)
Tuoteryhmä	3
Tullitariffin numero	73089098
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Lataukset



Alles online

[Asennusohje \(PDF\)](#)

CAD 2D (DXF)

[Mittapiirustus \(PDF\)](#)

CAD (DWG)

[Esite \(PDF\)](#)