

LORO-VERBUND-ANSCHLUßST.AN KA-MUFFE, LORO-Connection piece to KA-socket DN 100

Descrição

LORO-X compound pipe connector (from LORO-X pipe to KA socket and SML), consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN100




Dados do artigo

Código EAN	4038088035092
Classe ETIM	EC003024
Diâmetro nominal	DN 100
Medidas exteriores (AxLxP)	133 x 133 x 180 mm
Peso	2,20 Kg (STK)
Grupo de produtos	3
Número de pauta aduaneira	73089098
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Transferências



Alles online

[Instruções de instalação \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Desenho cotado \(PDF\)](#)
[CAD \(DWG\)](#)

[Brochura \(PDF\)](#)