

LORO-VERBUND-ANSCHLUßST.AN KA-ROHR,

LORO-Connection piece to KA-pipe DN 100

Kuvaus

LORO-X compound pipe connector (from KA pipe/SML pipe to LORO-X socket) consisting of inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, according to DIN EN 1123, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), DN100




Tuotetiedot

EAN-koodi	4038088035085
ETIM-luokka	EC003024
Nimellishalkaisija	DN 100
Ulkomitat (KxLxS)	133 x 133 x 180 mm
Paino	2,20 Kg (STK)
Tuoteryhmä	3
Tullitariffin numero	73089098
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

Doppelwandiges Abflußrohr, DN 40 - DN 150 bestehend aus: Innenrohr aus LORO-X Stahlabflußrohr, PU-Dämmschicht Baustoffklasse B2, FCKW-frei. Außenrohr aus LORO-X Stahlabflußrohr



Lataukset



Alles online

[Asennusohje \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Mittapiirustus \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[Esite \(PDF\)](#)

[BIM 3D \(STEP\)](#)