LX-VERBUNDROHR M. BEGLEITHEIZUNG DN100 3

LORO multilayer pipe with trace heating

Udbudstekst

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 3000 mm long, DN100, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m





Artikeldata

EAN-kode	**4038088039342**
ETIM Klasse	**EC010225**
Nominel diameter	**DN 100**
Nominel længde/grad	**3000**
Ydermål (HxBxL)	**156 x 133 x 3070 mm**
Vægt	**44,60 Kg (STK)**
Produktgruppe	**3**
Toldtarifnummer	**73063012**
Materiale / Farve	**Stahl feuerverzinkt, Silber**

Brugsanvisning

kein Verwendungshinweis notwendig

Downloads

Alles online

Måltegning (PDF)
Brochure (PDF)
CAD 2D (DXF)
CAD (DWG)