LX-VERBUNDROHR M. BEGLEITHEIZUNG DN100 3

LORO multilayer pipe with trace heating

Text pro výběrové řízení

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 3000 mm long, DN100, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m





Údaje o artiklu

EAN kód	4038088039342
ETIM třída	EC010225
Jmenovitý průměr	DN 100
Jmenovitá délka/stupeň	3000
Vnější rozměry (VxŠxD)	156 x 133 x 3070 mm
Hmotnost	44,60 Kg (STK)
Skupina produktů	3
Celní sazebník	73063012
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

kein Verwendungshinweis notwendig

Ke stažení

Alles online

Výkres rozměrů (PDF)
Prospekt (PDF)
CAD 2D (DXF)
CAD (DWG)