


LX-VERBUNDROHR M. BEGLEITHEIZUNG DN150 3

LORO multilayer pipe with trace heating

Tarjouspyyntöteksti

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 3000 mm long, DN150, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m




Tuotetiedot

EAN-koodi	4038088039366
ETIM-luokka	EC010225
Nimellishalkaisija	DN 150
Nimellispituus/-aste	3000
Ulkomitat (KxLxS)	241 x 219 x 3080 mm
Paino	90,00 Kg (STK)
Tuoteryhmä	3
Tullitariffin numero	73063018
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

kein Verwendungshinweis notwendig



Lataukset



Alles online

[Mittapiirustus \(PDF\)](#)

[CAD \(DWG\)](#)

[Esite \(PDF\)](#)

[CAD 2D \(DXF\)](#)