LX-VERBUNDROHR M. BEGLEITHEIZUNG DN150 3

LORO multilayer pipe with trace heating

Beskrivelsestekst

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 3000 mm long, DN150, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m





Artikkeldata

EAN-kode	**4038088039366**
ETIM-klasse	**EC010225**
Nominell diameter	**DN 150**
Nominell lengde/grad	**3000**
Utvendige mål (HxBxL)	**241 x 219 x 3080 mm**
Vekt	**90,00 Kg (STK)**
Produktgruppe	**3**
Tolltariffnummer	**73063018**
Materiale / Farge	**Stahl feuerverzinkt, Silber**

Bruksanvisning

kein Verwendungshinweis notwendig

Nedlastinger

Alles online

Måltegning (PDF)
Brosjyre (PDF)
CAD 2D (DXF)
CAD (DWG)