


LX-VERBUNDROHR M. BEGLEITHEIZUNG DN70 30

LORO multilayer pipe with trace heating

Besedilo za popis del

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 2000 mm long, DN70, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m




Podatki o izdelku

EAN koda	4038088039298
ETIM razred	EC010225
Nazivni premer	DN 70
Nazivna dolžina/stopinja	2000
Zunanje mere (VxŠxD)	125 x 102 x 2055 mm
Teža	18,40 Kg (STK)
Skupina izdelkov	3
Carinska tarifna številka	73063012
Material / Barva	Stahl feuerverzinkt, Silber

Opomba za uporabo

kein Verwendungshinweis notwendig



Prenosi



Alles online

[Merska risba \(PDF\)](#)

[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)

[CAD 2D \(DXF\)](#)