



## LX-VERBUNDROHR M. BEGLEITHEIZUNG DN100 2

LORO multilayer pipe with trace heating

### Text pre výberové konanie

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 2000 mm long, DN100, with self-regulating trace heating with connecting cable 3 x 1.5 mm<sup>2</sup>, cable length ca. 1 m



### Údaje o artikli

|                           |                             |
|---------------------------|-----------------------------|
| EAN kód                   | 4038088039304               |
| ETIM trieda               | EC010225                    |
| Menovitý priemer          | DN 100                      |
| Menovitá dĺžka/stupeň     | 2000                        |
| Vonkajšie rozmery (VxŠxH) | 156 x 133 x 2070 mm         |
| Hmotnosť                  | 32,00 Kg (STK)              |
| Skupina produktov         | 3                           |
| Colný sadzobník           | 73063012                    |
| Materiál / Farba          | Stahl feuerverzinkt, Silber |

### Pokyny na použitie

kein Verwendungshinweis notwendig

### Na stiahnutie



Alles online

[Rozmerový výkres \(PDF\)](#)

[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)

[CAD 2D \(DXF\)](#)