


LX-VERBUNDROHR M. BEGLEITHEIZUNG DN125 2

LORO multilayer pipe with trace heating

Texto de licitación

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 2000 mm long, DN125, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m




Datos del artículo

Código EAN	4038088039311
Clase ETIM	EC010225
Diámetro nominal	DN 125
Longitud/grado nominal	2000
Medidas exteriores (AxAxL)	191 x 168 x 2075 mm
Peso	43,00 Kg (STK)
Grupo de productos	3
Número de arancel aduanero	73063018
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

kein Verwendungshinweis notwendig



Descargas



Alles online

[Dibujo dimensional \(PDF\)](#)

[CAD \(DWG\)](#)

[Folleto \(PDF\)](#)

[CAD 2D \(DXF\)](#)