LX-VERBUNDROHR M. BEGLEITHEIZUNG DN150 2

LORO multilayer pipe with trace heating

Text pre výberové konanie

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 2000 mm long, DN150, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m





Údaje o artikli

EAN kód	4038088039328
ETIM trieda	EC010225
Menovitý priemer	DN 150
Menovitá dĺžka/stupeň	2000
Vonkajšie rozmery (VxŠxH)	241 x 219 x 2080 mm
Hmotnosť	60,00 Kg (STK)
Skupina produktov	3
Colný sadzobník	73063018
Materiál / Farba	Stahl feuerverzinkt, Silber

Pokyny na použitie

kein Verwendungshinweis notwendig

Na stiahnutie

Rozmerový výkres (PDF)
Prospekt (PDF)
CAD 2D (DXF)
CAD (DWG)

Alles online