


LX-VERBUNDROHR M. BEGLEITHEIZUNG DN150 2

LORO multilayer pipe with trace heating

Beskrivelsestekst

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 2000 mm long, DN150, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m




Artikkeldata

EAN-kode	4038088039328
ETIM-klasse	EC010225
Nominell diameter	DN 150
Nominell lengde/grad	2000
Utvendige mål (HxBxL)	241 x 219 x 2080 mm
Vekt	60,00 Kg (STK)
Produktgruppe	3
Tolltariffnummer	73063018
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

kein Verwendungshinweis notwendig



Nedlastinger



Alles online

[Måltgning \(PDF\)](#)

[CAD \(DWG\)](#)

[Brosjyre \(PDF\)](#)

[CAD 2D \(DXF\)](#)