


LORO-X COMPOUND PIPE WITH HEATING COIL, STANDARD TYPE

LORO multilayer pipe with trace heating

Text pro výběrové řízení

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 1000 mm long, DN70, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m with connecting cable 3 x 1.5 mm², cable length ca. 1 m




Údaje o artiklu

EAN kód	4038088025536
ETIM třída	EC010225
Jmenovitý průměr	DN 70
Jmenovitá délka/stupeň	1000
Vnější rozměry (VxŠxD)	125 x 102 x 1055 mm
Hmotnost	10,20 Kg (STK)
Skupina produktů	3
Celní sazebník	73063012
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

kein Verwendungshinweis notwendig



Ke stažení



Alles online

[Výkres rozměrů \(PDF\)](#)

[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)

[CAD 2D \(DXF\)](#)