


LORO-X COMPOUND PIPE WITH HEATING COIL, STANDARD TYPE

LORO multilayer pipe with trace heating

Текст за тръжна документация

LORO-X compound pipe consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 1000 mm long, DN125, with self-regulating trace heating with connecting cable 3 x 1.5 mm², cable length ca. 1 m with connecting cable 3 x 1.5 mm², cable length ca. 1 m




Данни за артикула

ЕАН код	4038088025550
ЕТИМ клас	EC010225
Номинален диаметър	DN 125
Номинална дължина/градус	1000
Външни размери (ВxШxД)	191 x 168 x 1075 mm
Тегло	24,20 Kg (STK)
Продуктова група	3
Митнически тарифен номер	73063018
Материал / Цвят	Stahl feuerverzinkt, Silber

Забележка за употреба

kein Verwendungshinweis notwendig



Изтегляния



Alles online

[CAD чертеж \(PDF\)](#)

[CAD \(DWG\)](#)

[Брошура \(PDF\)](#)

[CAD 2D \(DXF\)](#)