

LORO-VERBUNDROHR SILENT 3000 MM DN 40

LORO-Composite Pipe SILENT 3000 mm DN 40

Beskrivningstext

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 3000 mm long, DN40

Artikeldata

EAN-kod	4038088089897
ETIM-klass	EC010225
Nominell diameter	DN 40
Nominell längd/grad	3000
Yttermått (HxBxL)	89 x 89 x 3030 mm
Vikt	17,00 Kg (STK)
Produktgrupp	3
Tullnummer	73063012
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Nedladdningar


[Broschyr \(PDF\)](#)

Alles online