

## LORO-VERBUNDROHR SILENT 3000 MM DN 40

### LORO-Composite Pipe SILENT 3000 mm DN 40

#### Texto para caderno de encargos

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 3000 mm long, DN40

#### Dados do artigo

|                            |                             |
|----------------------------|-----------------------------|
| Código EAN                 | 4038088089897               |
| Classe ETIM                | EC010225                    |
| Diâmetro nominal           | DN 40                       |
| Comprimento/grau nominal   | 3000                        |
| Medidas exteriores (AxLxP) | 89 x 89 x 3030 mm           |
| Peso                       | 17,00 Kg (STK)              |
| Grupo de produtos          | 3                           |
| Número de pauta aduaneira  | 73063012                    |
| Material / Cor             | Stahl feuerverzinkt, Silber |

#### Nota de utilização

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

#### Transferências


[Brochura \(PDF\)](#)

Alles online