

## LORO-VERBUNDROHR SILENT 3000 MM DN 40

### LORO-Composite Pipe SILENT 3000 mm DN 40

#### Tekst przetargowy

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 3000 mm long, DN40

#### Dane artykułu

|                            |                             |
|----------------------------|-----------------------------|
| Kod EAN                    | 4038088089897               |
| Klasa ETIM                 | EC010225                    |
| Średnica nominalna         | DN 40                       |
| Długość/stopień nominalny  | 3000                        |
| Wymiary zewnętrzne (WxSxD) | 89 x 89 x 3030 mm           |
| Waga                       | 17,00 Kg (STK)              |
| Grupa produktów            | 3                           |
| Numer taryfy celnej        | 73063012                    |
| Materiał / Kolor           | Stahl feuerverzinkt, Silber |

#### Wskazówki dotyczące użytkowania

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

#### Pobieranie



Alles online

[Broszura \(PDF\)](#)