LORO-VERBUNDROHR SILENT 3000 MM DN 40

LORO-Composite Pipe SILENT 3000 mm DN 40

Texte de prescription

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 3000 mm long, DN40

Données de l'article

Code EAN	**4038088089897**
Classe ETIM	**EC010225**
Diamètre nominal	**DN 40**
Longueur/degré nominal	**3000**
Dimensions extérieures (HxLxP)	**89 x 89 x 3030 mm**
Poids	**17,00 Kg (STK)**
Groupe de produits	**3**
Numéro tarifaire douanier	**73063012**
Matériau / Couleur	**Stahl feuerverzinkt, Silber**

Note d'utilisation

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Téléchargements

Brochure (PDF)

Alles online