

LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET 3000 MM DN 50

LORO-Composite Pipe SILENT 3000 mm DN 50

Descrição

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 3000 mm long, DN50




Dados do artigo

Código EAN	4038088025574
Classe ETIM	EC010225
Diâmetro nominal	DN 50
Comprimento/grau nominal	3000
Medidas exteriores (AxLxP)	89 x 89 x 3038 mm
Peso	21,60 Kg (STK)
Grupo de produtos	3
Número de pauta aduaneira	73063012
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Transferências



Alles online

[Instruções de instalação \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Desenho cotado \(PDF\)](#)
[CAD \(DWG\)](#)

[Brochura \(PDF\)](#)