


LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET 3000 MM DN 150

LORO multilayer pipe SILENT 3000 mm DN 150

Description

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 3000 mm long, DN150



Données de l'article

Code EAN	4038088025611
Classe ETIM	EC010225
Diamètre nominal	DN 150
Longueur/degré nominal	3000
Dimensions extérieures (HxLxP)	219 x 219 x 3080 mm
Poids	93,60 Kg (STK)
Groupe de produits	3
Numéro tarifaire douanier	73063018
Matériau / Couleur	Stahl feuerverzinkt, Silber

Note d'utilisation

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Téléchargements



Alles online

[Notice d'installation \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Dessin dimensionnel \(PDF\)](#)
[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)