

LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET 2000 MM DN 50

LORO multilayer pipe SILENT 2000 mm DN 50

Beskrivelse

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 2000 mm long, DN50




Artikeldata

EAN-kode	4038088025628
ETIM Klasse	EC010225
Nominel diameter	DN 50
Nominel længde/grad	2000
Ydermål (HxBxL)	89 x 89 x 2038 mm
Vægt	14,70 Kg (STK)
Produktgruppe	3
Toldtarifnummer	73063012
Materiale / Farve	Stahl feuerverzinkt, Silber

Brugsanvisning

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Downloads



Alles online

[Installationsvejledning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Måltegning \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)