

LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET 2000 MM DN 100

LORO multilayer pipe SILENT 2000 mm DN 100

Beskrivelse

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 2000 mm long, DN100




Artikeldata

EAN-kode	4038088025642
ETIM Klasse	EC010225
Nominel diameter	DN 100
Nominel længde/grad	2000
Ydermål (HxBxL)	133 x 133 x 2070 mm
Vægt	33,20 Kg (STK)
Produktgruppe	3
Toldtarifnummer	73063012
Materiale / Farve	Stahl feuerverzinkt, Silber

Brugsanvisning

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus:Innenrohr mit Schallschutzfolie,PU-
Dämmschicht, Baustoffklasse B2, FCKW-
frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X
Stahlabflussrohr) Achtung: Sonderanfertigung - keine
Lagerware.



Downloads



Alles online

[Installationsvejledning \(PDF\)](#)

CAD 2D (DXF)

[Måltegning \(PDF\)](#)

CAD (DWG)

[Brochure \(PDF\)](#)