

LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET 2000 MM DN 200

LORO multilayer pipe SILENT pipe 1 1 socket 2,000 mm DN 200

Description

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 2000 mm long, DN200



Article information

EAN Code	4038088038284
ETIM Class	EC010225
Nominal diameter	DN 200
Nominal length/degree	2000
Outside measurements (HxWxL)	273 x 273 x 2120 mm
Weight	94,70 Kg (STK)
Product group	3
Customs tariff number	73063018
Material / Color	Stahl feuerverzinkt, Silber

Usage note

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Downloads



Alles online

[Installation \(PDF\)](#)

[Brochure \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)