# LORO-VERBUNDROHR SILENT 1000 MM DN 40

**LORO-Composite Pipe SILENT 1000 mm DN 40**

## Texte de prescription

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 1000 mm long, DN40

## Données de l'article

| | |
|---|---|
| Code EAN | **4038088089910** |
| Classe ETIM | **EC010225** |
| Diamètre nominal | **DN 40** |
| Longueur/degré nominal | **1000** |
| Dimensions extérieures (HxLxP) | **89 x 89 x 1030 mm** |
| Poids | **6,20 Kg (STK)** |
| Groupe de produits | **3** |
| Numéro tarifaire douanier | **73063012** |
| Matériau / Couleur | **Stahl feuerverzinkt, Silber** |

## Note d'utilisation

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

## Téléchargements

Notice d'installation (PDF)

Brochure (PDF)

Alles online