

LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET 1000 MM DN 50

LORO-Composite Pipe SILENT 1000 mm DN 50

Kuvaus

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 1000 mm long, DN50




Tuotetiedot

EAN-koodi	4038088025673
ETIM-luokka	EC010225
Nimellishalkaisija	DN 50
Nimellispituus/-aste	1000
Ulkomitat (KxLxS)	89 x 89 x 1038 mm
Paino	7,10 Kg (STK)
Tuoteryhmä	3
Tullitariffin numero	73063012
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Lataukset



Alles online

[Asennusohje \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[Mittapiirustus \(PDF\)](#)
[CAD \(DWG\)](#)
[Esite \(PDF\)](#)