LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET1000 MM DN 125

LORO-Composite Pipe SILENT 1000 mm DN 125

Description

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 1000 mm long, DN125



Données de l'article

Code EAN	**4038088025703**
Classe ETIM	**EC010225**
Diamètre nominal	**DN 125**
Longueur/degré nominal	**1000**
Dimensions extérieures (HxLxP)	**168 x 168 x 1075 mm**
Poids	**26,00 Kg (STK)**
Groupe de produits	**3**
Numéro tarifaire douanier	**73063018**
Matériau / Couleur	**Stahl feuerverzinkt, Silber**

Note d'utilisation

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Téléchargements

Notice d'installation (PDF)
Dessin dimensionnel (PDF)
Brochure (PDF)
CAD 2D (DXF)
CAD (DWG)

Alles online