LORO-VERBUNDROHR SILENT 500 MM DN 32

LORO-Composite Pipe SILENT 500 mm DN 32

Beskrivelsestekst

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 500 mm long, DN32



Artikkeldata

EAN-kode	**4038088094433**
ETIM-klasse	**EC010225**
Nominell diameter	**DN 32**
Nominell lengde/grad	**500**
Utvendige mål (HxBxL)	**89 x 89 x 525 mm**
Vekt	**2,40 Kg (STK)**
Produktgruppe	**3**
Tolltariffnummer	**73063012**
Materiale / Farge	**Stahl feuerverzinkt, Silber**

Bruksanvisning

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Nedlastinger

Alles online

Monteringsanvisning (PDF)
CAD 2D (DXF)
Måltegning (PDF)
CAD (DWG)
Brosjyre (PDF)