

LORO-VERBUNDROHR SILENT 500 MM DN 40

LORO-Composite Pipe SILENT 500 mm DN 40

Text pro výběrové řízení

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 500 mm long, DN40



Údaje o artiklu

EAN kód	4038088089927
ETIM třída	EC010225
Jmenovitý průměr	DN 40
Jmenovitá délka/stupeň	500
Vnější rozměry (VxŠxD)	89 x 89 x 530 mm
Hmotnost	3,30 Kg (STK)
Skupina produktů	3
Celní sazebník	73063012
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Ke stažení



Alles online

[Návod k instalaci \(PDF\)](#)

[Prospekt \(PDF\)](#)