

LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET 500 MM DN 70

LORO multilayer pipe SILENT 500 mm DN 70

Beskrivning

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 500 mm long, DN70




Artikeldata

EAN-kod	4038088025734
ETIM-klass	EC010225
Nominell diameter	DN 70
Nominell längd/grad	500
Yttermått (HxBxL)	84 x 84 x 555 mm
Vikt	5,20 Kg (STK)
Produktgrupp	3
Tullnummer	73063012
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

Silent för erhöjda Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Måttitning \(PDF\)](#)

[CAD \(DWG\)](#)

[Broschyr \(PDF\)](#)