

## LORO-VERBUNDROHR SILENT 250 MM DN 40

LORO-Composite pipe SILENT 250 mm DN 40

### Beskrivningstext

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 250 mm long, DN40



### Artikeldata

|                     |                             |
|---------------------|-----------------------------|
| EAN-kod             | 4038088089934               |
| ETIM-klass          | EC010225                    |
| Nominell diameter   | DN 40                       |
| Nominell längd/grad | 250                         |
| Yttermått (HxBxL)   | 89 x 89 x 280 mm            |
| Vikt                | 1,50 Kg (STK)               |
| Produktgrupp        | 3                           |
| Tullnummer          | 73063012                    |
| Material / Färg     | Stahl feuerverzinkt, Silber |

### Användningsanvisning

Silent für erhöhte Schallschutzanforderungen  
Doppelwandiges Abflussrohr, DN 40 - DN 150  
bestehend aus:Innenrohr mit Schallschutzfolie,PU-  
Dämmschicht, Baustoffklasse B2, FCKW-  
frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X  
Stahlabflussrohr) Achtung: Sonderanfertigung - keine  
Lagerware.

### Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)

[Broschyr \(PDF\)](#)