LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET250 MM DN 100

LORO multilayer pipe SILENT 250 mm DN 100

Descrição

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 250 mm long, DN100



Dados do artigo

Código EAN	4038088025796
Classe ETIM	EC010225
Diâmetro nominal	DN 100
Comprimento/grau nominal	250
Medidas exteriores (AxLxP)	133 x 133 x 320 mm
Peso	4,30 Kg (STK)
Grupo de produtos	3
Número de pauta aduaneira	73063012
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Transferências

Instruções de instalação (PDF)
Desenho cotado (PDF)
Brochura (PDF)
CAD 2D (DXF)
CAD (DWG)

Alles online