

LORO-VERBUNDROHR SILENT 1500 MM DN 32

LORO-Composite Pipe SILENT 1500 mm DN 32

Text pentru caietul de sarcini

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 1500 mm long, DN32




Date articol

Cod EAN	4038088094471
Clasă ETIM	EC010225
Diametru nominal	DN 32
Lungime/grad nominal	1500
Dimensiuni exterioare (îxLxA)	89 x 89 x 1525 mm
Greutate	7,20 Kg (STK)
Grupă de produse	3
Număr tarif vamal	73063012
Material / Culoare	Stahl feuerverzinkt, Silber

Notă de utilizare

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Descărcări



Alles online

[Instrucțiuni de montaj \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Desen CAD \(PDF\)](#)
[CAD \(DWG\)](#)

[Broșură \(PDF\)](#)