


LORO-X SILENT COMPOSITE PIPE WITH 1 SOCKET 1500 MM DN 70

LORO multilayer pipe SILENT 1500 mm DN 70

Popis

LORO-X compound pipe, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 1500 mm long, DN70



Údaje o artikli

EAN kód	4038088025833
ETIM trieda	EC010225
Menovitý priemer	DN 70
Menovitá dĺžka/stupeň	1500
Vonkajšie rozmery (VxŠxH)	84 x 84 x 1555 mm
Hmotnosť	14,20 Kg (STK)
Skupina produktov	3
Colný sadzobník	73063012
Materiál / Farba	Stahl feuerverzinkt, Silber

Pokyny na použitie

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Na stiahnutie



Alles online

[Návod na montáž \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Rozmerový výkres \(PDF\)](#)
[CAD \(DWG\)](#)

[Prospekt \(PDF\)](#)