

LORO-VERBUNDROHR-ABZW.SILENT 87 GR.

LORO-Composite pipe branch SILENT 87 degrees DN 40/40

Voce di capitolato

LORO-X compound pipe branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 87 degrees, DN40



Dati articolo

Codice EAN	4038088090022
Classe ETIM	EC003025
Diametro nominale	DN 40, DN 40
Lunghezza/grado nominale	87
Misure esterne (AxLxP)	135 x 89 x 168 mm
Peso	1,20 Kg (STK)
Gruppo prodotti	3
Numero tariffa doganale	73089098
Materiale / Colore	Stahl feuerverzinkt, Silber

Note d'uso

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Download



Alles online

[Istruzioni di installazione \(PDF\)](#)

[Brochure \(PDF\)](#)