

## LORO-X SILENT COMPOSITE BRANCH 87 DEGREE DN 200/200

### LORO-Composite pipe branch

#### Text pre výberové konanie

LORO-X compound pipe branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 87 degrees, DN200

#### Údaje o artikli

|                       |                             |
|-----------------------|-----------------------------|
| EAN kód               | 4038088038314               |
| ETIM trieda           | EC003025                    |
| Menovitý priemer      | DN 200, DN 200              |
| Menovitá dĺžka/stupeň | 87                          |
| Hmotnosť              | 22,40 Kg (STK)              |
| Skupina produktov     | 3                           |
| Colný sadzobník       | 73089098                    |
| Materiál / Farba      | Stahl feuerverzinkt, Silber |

#### Pokyny na použitie

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

#### Na stiahnutie



Alles online

[Návod na montáž \(PDF\)](#)

[Prospekt \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)