LORO-X SILENT COMPOSITE BRANCH 45 DEGREE DN 70/70

LORO-Composite pipe branch SILENT 45 degrees DN 70/70

Kuvaus

LORO-X compound pipe branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN70



Tuotetiedot

EAN-koodi	**4038088026083**
ETIM-luokka	**EC003025**
Nimellishalkaisija	**DN 70, DN 70**
Nimellispituus/-aste	**45**
Ulkomitat (KxLxS)	**102 x 207 x 255 mm**
Paino	**3,60 Kg (STK)**
Tuoteryhmä	**3**
Tullitariffin numero	**73089098**
Materiaali / Väri	**Stahl feuerverzinkt, Silber**

Käyttöohje

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Lataukset

Alles online

Asennusohje (PDF)
CAD 2D (DXF)
Mittapiirustus (PDF)
CAD (DWG)
Esite (PDF)