

LORO-X SILENT COMPOSITE BRANCH 45 DEGREE DN 70/70

LORO-Composite pipe branch SILENT 45 degrees DN 70/70

Descrizione

LORO-X compound pipe branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 45 degrees, DN70




Dati articolo

Codice EAN	4038088026083
Classe ETIM	EC003025
Diametro nominale	DN 70, DN 70
Lunghezza/grado nominale	45
Misure esterne (AxLxP)	102 x 207 x 255 mm
Peso	3,60 Kg (STK)
Gruppo prodotti	3
Numero tariffa doganale	73089098
Materiale / Colore	Stahl feuerverzinkt, Silber

Note d'uso

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Download



Alles online

[Istruzioni di installazione \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Disegno dimensionale \(PDF\)](#)
[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)