

LORO-X SILENT COMPOSITE REDUCED BRANCH 88 DEGREE DN 70/50

LORO-Composite pipe red. branches SILENT 87 degrees DN 70/50

Описание

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), sound insulation mat (attached to inner pipe) insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized) 87 degrees, DN70/50




Данни за артикула

ЕАН код	4038088026120
ETIM клас	EC003025
Номинален диаметър	DN 70, DN 50
Номинална дължина/градус	88
Външни размери (ВхШхД)	102 x 152 x 205 mm
Тегло	2,00 Kg (STK)
Продуктова група	3
Митнически тарифен номер	73089098
Материал / Цвят	Stahl feuerverzinkt, Silber

Забелешка за употреба

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus:Innenrohr mit Schallschutzfolie,PU-
Dämmschicht, Baustoffklasse B2, FCKW-
frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X
Stahlabflussrohr) Achtung: Sonderanfertigung - keine
Lagerware.



Изтегляния



Alles online

[Инструкция за монтаж \(PDF\)](#)

CAD 2D (DXF)

[CAD чертеж \(PDF\)](#)

CAD (DWG)

[Брошура \(PDF\)](#)