LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 40/32

LORO-Composite Pipe Red. branches SILENT 45 degrees DN 40/32

Bestektekst

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN40/32

Artikelgegevens

EAN-code	4038088093139
ETIM Klasse	EC003025
Nominale diameter	DN 40, DN 32
Nominale lengte/graad	45
Buitenafmetingen (HxBxL)	89 x 198 x 227 mm
Gewicht	0,60 Kg (STK)
Productgroep	3
Douanetariefnummer	73089098
Materiaal / Kleur	Stahl feuerverzinkt, Silber

Gebruiksaanwijzing

Silent für erhöhte Schallschutzanforderungen Doppelwandiges Abflussrohr, DN 40 - DN 150 bestehend aus:Innenrohr mit Schallschutzfolie,PU-Dämmschicht, Baustoffklasse B2, FCKW-frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.

Downloads

Installatiehandleiding (PDF)

Brochure (PDF)

Alles online