

## LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 40/32

LORO-Composite Pipe Red. branches SILENT 45 degrees DN 40/32

### Udbudstekst

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN40/32



### Artikeldata

|                        |                             |
|------------------------|-----------------------------|
| EAN-kode               | 4038088093139               |
| ETIM Klasse            | EC003025                    |
| Nominel diameter       | DN 40, DN 32                |
| Nominel<br>længde/grad | 45                          |
| Ydermål (HxBxL)        | 89 x 198 x 227 mm           |
| Vægt                   | 0,60 Kg (STK)               |
| Produktgruppe          | 3                           |
| Toldtarifnummer        | 73089098                    |
| Materiale / Farve      | Stahl feuerverzinkt, Silber |

### Brugsanvisning

Silent für erhöhte Schallschutzanforderungen  
Doppelwandiges Abflussrohr, DN 40 - DN 150  
bestehend aus:Innenrohr mit Schallschutzfolie,PU-  
Dämmschicht, Baustoffklasse B2, FCKW-  
frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X  
Stahlabflussrohr) Achtung: Sonderanfertigung - keine  
Lagerware.

### Downloads



Alles online

[Installationsvejledning \(PDF\)](#)

[Brochure \(PDF\)](#)