

LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 40/32

LORO-Composite Pipe Red. branches SILENT 45 degrees DN 40/32

Beskrivelsestekst

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN40/32



Artikkeldata

EAN-kode	4038088093139
ETIM-klasse	EC003025
Nominell diameter	DN 40, DN 32
Nominell lengde/grad	45
Utvendige mål (HxBxL)	89 x 198 x 227 mm
Vekt	0,60 Kg (STK)
Produktgruppe	3
Tolltariffnummer	73089098
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus:Innenrohr mit Schallschutzfolie,PU-
Dämmschicht, Baustoffklasse B2, FCKW-
frei,Außenrohr (Innenrohr- und Außenrohr aus LORO-X
Stahlabflussrohr) Achtung: Sonderanfertigung - keine
Lagerware.

Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)

[Brosjyre \(PDF\)](#)