

LORO-X SILENT COMPOSITE REDUCING BRANCH 45 DEGREE DN 50/40

LORO-Composite Pipe Red. branches SILENT 45 degrees DN 50/40

Description

LORO-X compound pipe reducing branch, SILENT version, for increased sound-damping, consisting of: Inner pipe (LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown), insulation layer (PU hard foam B2, CFC-free) and outer pipe (LORO-X pipe, hot-dip galvanized), 45 degrees, DN50/40




Article information

EAN Code	4038088093153
ETIM Class	EC003025
Nominal diameter	DN 50, DN 40
Nominal length/degree	45
Outside measurements (HxWxL)	89 x 198 x 227 mm
Weight	1,50 Kg (STK)
Product group	3
Customs tariff number	73089098
Material / Color	Stahl feuerverzinkt, Silber

Usage note

Silent für erhöhte Schallschutzanforderungen
Doppelwandiges Abflussrohr, DN 40 - DN 150
bestehend aus: Innenrohr mit Schallschutzfolie, PU-Dämmschicht, Baustoffklasse B2, FCKW-frei, Außenrohr (Innenrohr- und Außenrohr aus LORO-X Stahlabflussrohr) Achtung: Sonderanfertigung - keine Lagerware.



Downloads



Alles online

[Installation \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[CAD drawing \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)